

COIL TUBING PRODUCTS

External Dimple Connector – 100 Series

The Coil Solutions External Dimple Connector was designed to attach the BHA to the end of the coil.

The Dimple Connector is secured to the outside of the coiled tubing by a series of set screws that seat a pattern of impressions created with a special design dimpling tool.

- Fast & easy to redress
- High torque, high tensile applications
- Used for drilling, milling, and fracturing
- Slimline applications



*Note. All values are rated for STD material.

Coil Size	1 ½"	1 ¾"	2"	2 ⅜"	2 ½"	2 ⅞"
Tool OD (in)	2.125	2.250	2.875	2.875	3.625	3.875
Connections	1 ½" AMMT	1 ½" AMMT	2 ⅜" PAC	2 ⅜" PAC	2 ⅜" PAC	2 ⅜" REG
Tensile Strength (lbs)	107,000	81,000	120,000	140,000	200,000	324,000
Torsional Strength (ft/lbs)	1,600	1,600	4,000	4,000	4,000	5,810
ID (in)	1.00	1.00	1.375	1.375	1.375	1.00
Length (in)	8.0	7.0	7.750	9.125	9.125	8.50
Working Pressure (psi)	8,000	8,000	8,000	8,000	8,000	10,000

*Other sizes and thread variations upon request.

For Further Information Please Contact:

Salesusa@coilsolutions.com – USA Sales@coilsolutions.com – Canada www.coilsolutions.com