

COIL TUBING PRODUCTS

Grapple x Knuckle x Grapple Connector - 50 Series

Coil Solutions Grapple x Knuckle x Grapple Connector was designed to be used when spooling coil from reel to reel. The Knuckle design feature allows for flexibility when needing to pass through the gooseneck and injector without having to disconnect.

- Quick connection from coil to coil for spooling
- Can be used to thread coil over gooseneck and through injector
- Light pulling of coil from the well
- No welding required to spool coil
- Less down time
- No welding near well head



*Note. All values are rated for STD material.

| Coil Size (in) | 2" | 2 3/8" | 2 5/8" | 2 7/8" | 3 1/4" | 3 1/2" |
|------------------------|-----------|-----------|-----------|-----------|-----------|-----------|
| Wall Thickness (in) | .109-.204 | .125-.250 | .175-.250 | .156-.276 | .156-.276 | .175-.300 |
| Tensile Strength (lbs) | 19,000 | 32,000 | 41,000 | 40,000 | 36,000 | 32,000 |
| Length (in) | 21 | 22 | 23 | 23 | 23 | 25 |

*Other sizes and variations upon request.

For Further Information Please Contact:

Salesusa@coilsolutions.com – USA Sales@coilsolutions.com – Canada www.coilsolutions.com