

# COIL TUBING PRODUCTS

## Knuckle Joint Assembly - 1400 Series

The Coil Solutions Knuckle Joint was designed to provide additional flexibility to the tool string and allows tools to be run in restricted or highly deviated wells.

- 360 degree rotation
- Flow through capability
- Angular of 15 degrees



\*Note. All values are rated for STD material.

<b>Tool OD (in)</b>	<b>1.688</b>	<b>1.750</b>	<b>2.125</b>	<b>2.875</b>
<b>Connections</b>	<b>1" AMMT</b>	<b>1" AMMT</b>	<b>1 ½" AMMT</b>	<b>2 ¾" PAC</b>
<b>Tensile Strength (lbs)</b>	<b>20,000</b>	<b>30,000</b>	<b>40,000</b>	<b>75,000</b>
<b>ID (in)</b>	<b>.625</b>	<b>.656</b>	<b>.875</b>	<b>.750</b>
<b>Length (in)</b>	<b>9.435</b>	<b>9.435</b>	<b>11.125</b>	<b>14.56</b>
<b>Working Pressure (psi)</b>	<b>10,000</b>	<b>10,000</b>	<b>10,000</b>	<b>10,000</b>

\*Other sizes and thread variations upon request.

**For Further Information Please Contact:**

Salesusa@coilsolutions.com – USA Sales@coilsolutions.com – Canada [www.coilsolutions.com](http://www.coilsolutions.com)