

COIL TUBING PRODUCTS

NO-GO – 400 Series

The Coil Solutions NO-GO is installed at the top of the Bottom Hole Assembly to ensure string tagging on the stripper when removing service tools from the well bore.

- Hardened body
- Multi-function crossover
- Long lasting no-go stop
- Can be placed in tool string in multiple places for skid saver



*Note. All values are rated for STD material.

| | | | | | | |
|------------------------------------|--------------|------------|--------------|--------------|--------------|--------------|
| Tool Body O.D (in) | 1.250 | 1.5 | 1.688 | 2.125 | 2.375 | 2.875 |
| Tool No-Go OD (in) | 1.250 | 1.750 | 2.0 | 2.50 | 2.75 | 3.250 |
| Connections | ¾ MT | 1 MT | 1 MT | 1½ MT | 1½ MT | 2 ¾" PAC |
| Tensile Strength (lbs) | 29,000 | 52,000 | 61,000 | 63,000 | 80,000 | 170,000 |
| Torsional Strength (ft/lbs) | 500 | 550 | 630 | 1,400 | 1,400 | 4,500 |
| ID (in) | .625 | .750 | .750 | 1.0 | 1.0 | 1.375 |
| Length (in) | 5.20 | 5.50 | 5.50 | 7.50 | 7.50 | 10.375 |
| Working Pressure (psi) | 10,000 | 10,000 | 10,000 | 10,000 | 10,000 | 10,000 |

*Other sizes and thread variations upon request.

For Further Information Please Contact:

Salesusa@coilsolutions.com – USA Sales@coilsolutions.com – Canada www.coilsolutions.com