

# COIL TUBING PRODUCTS

## Quick Connect - 820 Series

The Coil Solutions Quick Connect was designed to allow the tool string to be assembled in two manageable sections.

The Quick Connect can be connected over the wellhead without turning the Bottom Hole Assembly. It's useful when it is difficult to rotate tools to engage threads and best suited for long string applications. This tool also plays a fundamental role in any coil tubing deployment system.

- High tensile and torque strength
- Easy & Quick installation
- Minimal rotation needed to slide together
- Used for milling, drilling, fishing and all service applications
- Ideal for use in make up and running of velocity or gas lift strings.



\*Note. All values are rated for STD material.

Tool OD (in)	1.688	2.125	2.875	3.125
Connections	1" AMMT	1 ½" AMMT	2 ¾" PAC	2 ¾" REG
Tensile Strength (lbs)	36,000	40,000	90,000	135,000
Torsional Strength (ft/lbs)	650	1,100	3,400	5,400
ID (in)	.500	.812	1.125	1.016
Length (in)	15.875	18.0	18.0	18.0
Working Pressure (psi)	10,000	10,000	10,000	10,000

\*Other sizes and thread variations upon request.

**For Further Information Please Contact:**

Salesusa@coilsolutions.com – USA Sales@coilsolutions.com – Canada [www.coilsolutions.com](http://www.coilsolutions.com)