

COIL TUBING PRODUCTS

New and Patented

CSI SELECTIVE ABRASIVE PERFORATOR 6200 Series

The Coil Solutions SELECTIVE ABRASIVE PERFORATOR is designed to increase efficiency during abrasive perforating, especially multi-stage fracturing operations. Flow can be selectively diverted from the straight-through path of the BHA to the abrasive jetting housing and back to the straight-through path again. The changing between modes is possible an unlimited number of times utilizing a single (conventional) direction of flow. This allows the use of standard double flapper check valves in the BHA for improved safety when used on live well interventions, while still permitting two BHA modes that previously required two directions of flow to enable.

Features

- Various casing and tubing sizes
- Unlimited function of tool
- Tools for all well conditions
- Ease of passage through restrictions and prevents sticking
- Can be adapted to existing bottom hole assemblies



*Note: All values are rated for 80K material.

Tool OD	2-1/4"	2-7/8"	3-1/8"
Connections	1-1/2" AMMT	2-3/8" PAC	2-3/8" Reg
Tensile Strength (lbs)	53,000	96,000	135,500
Torsional Strength (ft-ib)	1,050	2,500	3,850
ID (in)	N/A	N/A	N/A
Length (in)	40.188	42.813	45.188
Working Pressure (psi)	5,000	5,000	5,000

*Other sizes and thread variations available upon request.

For Further Information Please Contact:

Salesusa@coilsolutions.com - USA

Sales@coilsolutions.com – Canada