

# COIL TUBING PRODUCTS

## Sleeved Dimple Connector - 270 Series

The Coil Solutions Sleeved Dimple Connector was designed to attach the BHA to the end of the coil.

The internal dimple connector is secured to the inside of the coil tubing with the outer shell dimpled to the outer coil tubing

- Robust connector
- Difficult well bores
- Dependable
- Easy to change up coil wall thickness
- Heavy tensile and torque loads are possible
- Accommodate the harshest conditions
- Minimal downtime
- Interchangeable dimple inserts



\*Note. All values are rated for STD material.

Coil Tubing O.D (in)	2	2.375	2.625	2.875
Tool OD (in)	2.875	2.875	3.125	3.375
Connections	2 3/8 PAC	2 3/8 PAC	2 3/8 PAC	2 3/8 PAC
Tensile Strength (lbs)	100,000	120,000	120,000	120,000
Torsional Strength (ft/lbs)	5,500	5,500	5,500	5,500
ID (in)	1.125	1.375	1.375	1.375
Length (in)	13.75	13.75	13.75	13.75
Working Pressure (psi)	10,000	10,000	10,000	10,000

\*Other sizes and thread variations upon request

**For Further Information Please Contact:**

Salesusa@coilsolutions.com – USA Sales@coilsolutions.com – Canada [www.coilsolutions.com](http://www.coilsolutions.com)