

COIL TUBING PRODUCTS

Wash Shoes – 400 Series

The Coil Solutions Wash Shoe was designed to clean the inside of well tubulars, while flowing through the nozzles a jetting action occurs while allowing the removal of residue such as salt, sand, mud, rust and scale.

- High velocity nozzles
- Variety of port angles and sizes

*Different configurations of nozzles can be ordered to best suit job applications.



*Note. All values are rated for STD material.

Tool OD (in)	1.5	1.688	1.75	2.0	2.875	3.125
Connections	1" AMMT	1" AMMT	1" AMMT	1 1/2" AMMT	2 3/8" PAC	2 3/8" REG
Tensile Strength (lbs)	68,000	68,000	68,000	127,000	238,000	375,000
Torsional Strength (ft/lbs)	765	765	765	1770	4800	8000
ID (in)	3/4	3/4	3/4	1	1.375	1
Length (in)	VARIOUS	VARIOUS	VARIOUS	VARIOUS	VARIOUS	VARIOUS
Working Pressure (psi)	10,000	10,000	10,000	10,000	10,000	10,000

*Other sizes and thread variations upon request.

For Further Information Please Contact:

Salesusa@coilsolutions.com – USA Sales@coilsolutions.com – Canada www.coilsolutions.com